



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
23.06.2004 Bulletin 2004/26

(51) Int Cl.7: **F21S 8/00, F21V 19/00,**
F21Y 101/02, F21W 131/103,
F21S 9/03, F21V 9/00,
F21V 29/00

(21) Application number: **03017665.5**

(22) Date of filing: **13.08.2003**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR
Designated Extension States:
AL LT LV MK

(30) Priority: **19.12.2002 JP 2002383448**

(71) Applicants:
• **Toshiji Kishimura**
Sagamihara-shi, Kanagawa-ken (JP)
• **Shoo Iwasaki**
Saitama-shi, Saitama-ken (JP)

(72) Inventors:
• **Kishimura, Toshiji**
Sagamihara-shi, Kanagawa-ken (JP)
• **Kishimura, Harumi**
Sagamihara-shi, Kanagawa-ken (JP)

• **Matsuno, Yasuhisa**
Yamato-shi, Kanagawa-ken (JP)
• **Abe, Satoshi**
Machida-shi, Tokyo-to (JP)
• **Takahashi, Toshifumi**
Sagamihara-shi, Kanagawa-ken (JP)
• **Tsunashima, Toshiyuki**
Machida-shi, Tokyo-to (JP)
• **Osawa, Masakatsu**
Sakai-shi, Osaka-fu (JP)
• **Hotta, Noboru**
Miyoshi-machi, Iruma-gun, Saitama-ken (JP)

(74) Representative: **Geyer, Ulrich F., Dr. Dipl.-Phys.**
WAGNER & GEYER,
Patentanwälte,
Gewürzmühlstrasse 5
80538 München (DE)


(54) **Light source for white color LED lighting and white color led lighting device**

(57) A white LED lighting device and a light source (3) for white LED lighting that enable an energy-saving, maintenance-free operation while ensuring ample illuminance.

Structure of a light source (3) for white LED lighting, constituted by: inserting and holding a plurality of white LED elements (11) in holding holes in a reflective plate (9), said plate (9) being constituted by providing a required number of said holding holes, in a matrix-like ar-

ray of prescribed pitch, in a plate (9) of shape corresponding to the illuminating surface of a lamp body; fixing said plurality of white LED elements at locations 2 to 4 mm behind their respective electrode portions; attaching the positive and negative terminals of the white LED elements to a base plate (10) for the LED elements, said base plate (10) being disposed parallel to and directly behind the reflective plate (9); and forming, at the positive and negative terminals, a series-parallel electrical network suitable for the applied voltage.

FIG. 2



Description**Field of the Invention**

[0001] The present invention relates to a white LED lighting device suitable for application to illumination lamps, and specifically to street lamps installed in public places such as streets and parks. The invention also relates to a light source for white LED lighting, for use as the light source in the aforesaid lighting device.

Description of Related Art

[0002] Illumination in streets and parks has conventionally been provided exclusively by incandescent lamps, mercury lamps and fluorescent lamps. However, because these light sources have a relatively high power consumption, the utilization of light emitting diodes (LEDs), which consume much less electric power than fluorescent lamps, has been studied as a means of saving energy. Nevertheless, due to some of their characteristics, such as strong directivity (being a point light source) and the glaring quality of their light, LEDs are not regarded as suitable for outdoors and other types of lighting and hence have not become widely popular in such applications. There are, however, some examples of prior art relating to LED lighting devices in application to indoor and outdoor use (see, for example, Reference 1 below).

[0003] In response to this situation, the present inventors have previously proposed a novel lighting device which uses LEDs as its light source and which will provide an LED lighting device that will save energy and also be more suitable for streetlights etc. (see, for example, Reference 2 below).

Reference 1:

[0004] Japanese Unexamined Patent Application Publication No. 11-213730 (p.2-3, paragraphs 9-14, FIGS.1, 2 and 3)

Reference 2:

[0005] Japanese Patent Application No. 2002-007762 (p.5-7, paragraphs 8-12, FIGS. 1 and 2)

[0006] The lighting device of Reference 1 has a plurality of LEDs and is provided with a hollow light-guide plate directly below these LEDs. It is also provided with a support for supporting this light-guide plate along its center axis. A diffusion layer having diffuse reflection characteristics and diffuse transmission characteristics is formed on an inner surface of the light guiding part of the light-guide plate, and a diffuse reflection layer is formed on a surface of the support. The LEDs are arranged along the upper end of the light guiding part.

[0007] However, numerous problems are encountered in connection with illuminance and product cost in

the case of this Reference 1 lighting device. Namely, in order to obtain a planar light source from a point light source LEDs, such a lighting device requires a special structure, namely: "provision of (i) a light-guide plate for a plurality of LEDs, this light-guide plate having a light guiding portion obtained by forming, on its inner surface, a diffusion layer having diffuse reflection characteristics and diffuse transmission characteristics, and (ii) a diffuse reflection layer parallel to this light-guide plate".

This requirement not only leads to a higher complexity of structure but also results in optical attenuation in the transparent light-guide plate, leading to poor efficiency since a large number of LEDs is needed to obtain a sufficient illuminance. Moreover, a globe to cover these parts is essential for outdoor applications.

[0008] On the other hand, in the Reference 2 lighting device (hereinafter termed the "previously proposed lighting device"), a plurality of LED elements are fitted in a distributed arrangement by being removably inserted in a bullet-shaped hollow container-like LED holder unit having a 5-layer structure, said LED holder unit being mounted, integrally and coaxially with a removable lamp base, on a general-purpose socket; wherein electrical connection and disconnection from the lamp base can be achieved by insertion and removal of these LED elements; and a transparent, bullet-shaped cover is removably mounted on the outside thereof so as to form an illumination light with an overall bullet-shaped lamp.

[0009] Although the previously proposed lighting device having this structure achieves its intended object of providing an energy-saving light, a number of problems still remain to be solved. One of these is the risk of excessive stimulation to pedestrians' eyes due to the rather high intensity of individual lights, resulting from a structure in which point light source LED elements are distributed around the periphery of the LED holder unit. Another problem is that because a conventional LED element is highly directive (i.e., light is output over a narrow angle), it is difficult to obtain a wide overall spread of light. In other words, the irradiation range (i.e., the illuminated area) per lighting device is small, with the result that more lighting units have to be used to illuminate a unit area.

[0010] The present invention has been made in the light of the above-mentioned facts. It is accordingly an object of the present invention to provide a white LED lighting device such that (i) the lighting unit configuration and design promotes the dispersion of emitted light, (ii) ample illuminance can be guaranteed without increasing the number of LED elements, and (iii) an energy-saving and maintenance-free lighting device can be obtained. It is a further object of the invention to provide a light source for white LED lighting which is optimal for use in said white LED lighting device.

Summary of the Invention

[0011] To achieve the above-mentioned objects, the

present invention as claimed in Claim 1 provides for a method of assembling a light source for white LED lighting, said method comprising the steps of: (i) inserting and holding a plurality of white LED elements 11 in holding holes in reflective plate 9, said plate being constituted by providing a required number of these holding holes, in a matrix-like array of prescribed pitch, in a plate of a shape corresponding to the illuminating surface of lamp body 1; (ii) fixing these white LED elements 11 at locations 2 to 4 mm behind their respective electrode portions 12; (iii) attaching the positive and negative terminals of white LED elements 11 to base plate 10 for the LED elements, said base plate being disposed parallel to and directly behind reflective plate 9; and (iv) forming, at the positive and negative terminals, a series-parallel electrical network suitable for the applied voltage.

[0012] According to this invention, by providing common reflective plate 9 at a location 2 to 4 mm behind the electrode portions of white LED elements 11 arranged in a matrix-like array of prescribed pitch, and due to the apparent increase in the number of white LED elements 11 and the effective optical reflection an efficient and loss-free frontal irradiation is provided. This makes it possible to maintain ample illuminance while minimizing the number of white LED elements 11. Accordingly, this light source for white LED lighting is advantageous in application to white LED lighting devices such as street-lights.

[0013] To achieve the above-mentioned objects, the present invention as claimed in Claim 2 is a white LED lighting device consisting of: (A) lamp body 1 provided with lamp casing 7, colourless transparent globe 8 matchingly fixed to an opening in the bottom of this lamp casing 7, light source 3 for white LED lighting housed in lamp casing 7, and light source controller 6 likewise housed in lamp casing 7; (B) lamp support 2 for supporting lamp body 1 in an attitude or position such that the illuminating surface of the lamp body is directed downward and its axis in the longer or longitudinal direction extends forwards with a slight upward tilt; and (C) power source device 4 housed in the lower part of lamp support 2 and serving to supply electric power to light source 3 for white LED lighting; this white LED lighting device being characterized in that: (D) lamp casing 7 and globe 8 have, in those parts facing light source 3 for white LED lighting, a transverse sectional shape which is rectangular in rear portions 7A and 8A that lie towards mounting base 13, the sides of said rectangular shape which are parallel to the above-mentioned longer direction being the short sides, and which is an elongated trapezoid in front portions 7B and 8B that are adjacent to the rear portions; (E) the inside of the illuminating surface of globe 8 is smooth surface 17, the outside is longitudinally banded concavo-convex surface 18 consisting of adjoining ridges and valleys alternating in succession with a pitch of a few millimetres, and the illuminating surface of globe 8 as a whole is formed as a curved plate

with bilateral symmetry whereof the bottom is the center line in the above-mentioned longer direction; (F) light source 3 for white LED lighting is constituted by: (i) inserting and holding a plurality of white LED elements 11 in holding holes in reflective plate 9, this plate providing a required number of these holding holes in the form of a multi-row, multi-column array of prescribed pitch; (ii) fixing white LED elements 11 at locations 2 to 4 mm behind their respective electrode portions 12; (iii) attaching the positive and negative terminals of white LED elements 11 to base plate 10 for the LED elements, this base plate being disposed parallel to and directly behind reflective plate 9; and (iv) forming, at the positive and negative terminals, a series-parallel electrical network suitable for the applied voltage; (G) reflective plate 9 and base plate 10 for the LED elements in rear portions 7A and 8A are formed into a bent plate having a wide half-angled gutter shape corresponding to the above-mentioned curved plate; (H) reflective plate 9 and base plate 10 for the LED elements in front portions 7B and 8B are formed into an elongated trapezoidal flat plate corresponding to the abovementioned curved plate; and (I) the intrinsic irradiation range of lamp body 1 is enlarged on the basis of a synergism between the optical reflection capability of reflective plate 9 and the optical refraction capability of the corrugations and curved plate of globe B.

[0014] The present invention, as described above, provides a design which is suitable for outdoor lighting devices such as streetlights. This suitability derives from the fact that the illuminating surface of globe 8 has overall a "thick quasi-T" shape consisting of a wide rectangle at rear portion 8A and a narrower tapered trapezoid at front portion 8B, thereby giving light distribution characteristics wherein maximum brightness is obtained immediately beneath the lighting device and brightness decreases gradually towards the periphery. The invention also creates a synergism between the optical reflection capability, provided by reflective plate 9 and restricted to the forwards direction, and the optical refraction and diffusion capability provided by the corrugations and curved plate of globe B. On the basis of the above-mentioned design and synergism, the effective irradiation range of the present invention as projected onto the ground - measuring this range outwards from a point directly below the lighting device - is an approximately elliptical shape whereof the width is greater than the length from front to back. This is evident from a diagram of actual measurements showing illuminance distribution, to be described hereinafter. Accordingly, the present invention can provide an illuminance distribution with an enlarged irradiation range and which is therefore ideal for streetlights. Moreover, the present invention can provide a lighting device which compares favorably with a conventional fluorescent light in terms of energy consumption. This is because it is clearly different from a cluster of spotlights or the like, in that the entire illuminating surface of globe 8 shines with a uni-

form brightness which is gentle on the eyes.

[0015] To achieve the above-mentioned objects, the present invention as claimed in Claim 3 is the white LED lighting device of Claim 2, wherein solar cell 5 is mounted and fixed at the upper end of lamp support 2; power source device 4 is provided with a storage battery; and light source controller 6 is provided with automatic voltage sensing means for sensing the output voltage of solar cell 5, and with automatic electrical storage means which uses the automatic voltage sensing means to cause electric power obtained from solar cell 5 to accumulate in the storage battery.

[0016] The present invention, as described in the previous paragraph, eliminates the need to lay power cables. This is because all the electric power required to power the lighting device during the night can be supplied by means of solar energy alone. The invention therefore also makes a significant contribution to reducing the consumption of electric power.

[0017] To achieve the above-mentioned objects, the present invention as claimed in Claim 4 is the white LED lighting device of Claim 3, wherein lamp support 2 is formed from a hollow pipe and provided with an air vent in the pipe wall close to the upper end, thereby enabling the hollow portion to produce a chimney effect so that heat generated by ambient air temperature can escape.

[0018] The present invention, as described in the previous paragraph, prevents temperature rise in the storage battery housing space, such a temperature rise having a potentially adverse effect on the battery, thereby extending battery life and improving the reliability of the white LED lighting device.

[0019] To achieve the above-mentioned objects, the present invention as claimed in Claim 5 is the white LED lighting device of Claim 3 or Claim 4, wherein lamp body 1 is provided with metal heat shield plate 16 mounted in the form of a sunshade directly above lamp casing 7 but leaving a slight air gap between the heat shield plate and the lamp casing. Further, the present invention as claimed in Claim 6 is the white LED lighting device of Claim 5, wherein lamp body 1 is provided with air inlets 19 and air outlets 20 in the rear and side faces of the side plate of rear portion 7A of lamp casing 7.

[0020] The white LED lighting device according to the invention as claimed in Claim 5 and Claim 6 suppresses temperature rise inside lamp body 1 during direct exposure to sunlight and during high summer temperatures, thereby stabilizing the performance of light source controller 6 and white LED elements 11, which are sensitive to temperature conditions, and improving device reliability.

Brief Description of the Drawings

[0021]

FIG. 1 is an overall view of a white LED lighting device according to an embodiment of this invention,

with FIG. 1(B) being a front view and FIG. 1(A) a right side view.

FIG. 2 is a side view of lamp body 1 of FIG. 1.

FIG. 3 is a bottom view of lamp body 1 of FIG. 1.

FIG. 4 is a rear view of lamp body 1 of FIG. 1.

FIG. 5 is an exploded perspective view of lamp body 1 of FIG. 1, seen in an angle from below.

FIG. 6 is a perspective view of lamp body 1 of FIG. 1, seen from the side.

FIG. 7 is a schematic vertical sectional view looking through the width of the rear portion of lamp body 1 of FIG. 1.

FIG. 8 is an enlarged partial view of light source 3 for white LED lighting, shown in FIG. 7.

FIG. 9 shows the illuminance distribution as measured during operation of a white LED lighting device according to an embodiment of the invention.

Description of Preferred Embodiment

[0022] An embodiment of the invention will now be described with reference to the accompanying drawings. FIG. 1 is an overall view of a white LED lighting device according to this embodiment, with FIG. 1(B) being a front view and FIG. 1(A) a view from the right side. The white LED lighting device illustrated in FIG. 1 comprises a lamp body 1, a lamp support 2, a power source device 4 and a solar cell 5. Lamp support 2 is for example an upright single-column stainless steel support composed of a lower bearing portion 15 and a pole portion 21, and has a protruding support arm 14 situated either on an intermediate portion of the support but nearer arranged to the top, as illustrated in FIG. 1, or at the top of the support. Lamp support 2 may be used, for example, as a street light support, in which case it is erected on the pedestrian sidewalk near the roadway shoulder, with support arm 14 projecting out over the sidewalk.

[0023] Power source device 4 is provided with the purpose of supplying electric power to light source 3 for white LED lighting (hereinafter termed simply "light source 3"). Light source 3 is located in lamp body 1 and will be subsequently described. A storage battery such as a long-life control valve type lead storage battery is used and this is housed in a prescribed vacant space inside lower bearing portion 15 which constitutes the bottom of support 2. It may be noted that it is also feasible to provide power source device 4 with an inverter (a DC-to-AC converter) in addition to the above-mentioned storage battery, so that in the event of emergency operation being necessary, electric power can be received from a low-voltage distribution line.

[0024] Solar cell 5 is installed on the top of lamp support 2, being fixed in a direction and at an angle of inclination such that it readily receives the maximum amount of sunlight. Solar cell 5 is selected from the three types available (polycrystalline, singlecrystal, single-crystal/amorphous), a suitable type being selected in accordance with installation conditions. A circuit is constructed

in such manner that the power obtained from solar cell 5 is accumulated in storage battery 4 via light source controller 6, which is not illustrated in FIG. 1 but will be described hereinafter. It may be noted that solar cell 5 is not essential and that a lighting device wherein only lamp body 1 is mounted on lamp support 2 and which is adapted to receive power from a power distribution line, is also within the scope of this invention.

[0025] Lamp body 1 has an outer casing with a "thick quasi-T" shape which is longer in the front-to-back depth direction than in the left-to-right width direction, this outer casing being composed of lamp casing 7 and colorless transparent globe 8 matchingly fixed to an opening in the bottom of lamp casing 7. Lamp casing 7 is made of stainless steel and globe 8 is made of acrylic resin. Lamp body 1 is supported on lamp support 2 by fitting and fixing mounting base 13, which projects integrally at the rear of lamp casing 7, to support arm 14. Lamp body 1 is for example fixed in a position approximately 3.5 m directly above the sidewalk and in a position such that its illuminating surface is directed downward and its axis in the longitudinal direction extends forwards with a slight upward tilt.

[0026] FIG. 2, FIG. 3 and FIG. 4 show respectively a side view, a bottom view and a rear view of lamp body 1 of FIG. 1. FIG. 5 is an exploded perspective view of lamp body 1 seen in an angle from below. FIG. 6 is likewise a perspective view of lamp body 1 but seen from the side. FIG. 7 is a schematic vertical sectional view looking through the width of the rear portion of lamp body 1. FIG. 8 is an enlarged partial view of light source 3 shown in FIG. 7.

[0027] The structure of lamp body 1 of a white LED lighting device according to an embodiment of this invention will now be described. Lamp body 1 has lamp casing 7, globe 8, light source 3 and light source controller 6. Lamp casing 7 and globe 8, which constitute the outer casing of lamp body 1, have, in those parts facing light source 3 which is housed inside the casing, a transverse sectional shape which is rectangular in rear portions 7A and 8A that lie towards mounting base 13, the sides of said rectangular shape which are parallel to the longer direction from front to back being the short sides, and which is a slender (narrower than rear portions 7A and 7B) tapering trapezoid in front portions 7B and 8B that lie integrally adjacent to the rear portions. When assembling lamp body 1, lamp casing 7 is placed on top relative to globe 8 and the opening portions of these two parts are joined together. Globe edge frame 22 made of stainless steel and fitted to the rim of globe 8 is then fitted inside the rim of lamp casing 7 to form an outer casing with a watertight integral structure obtained by the use of some fixing means such as clamping screws.

[0028] As reference to FIG. 5 and FIG. 7 makes evident, the inside of the illuminating surface of globe 8 is a smooth surface 17; the outside is longitudinally banded concavo-convex surface 18 consisting of adjoining

ridges and valleys alternating in succession with a pitch of a few millimetres, for example 5 mm; and the illuminating surface of the globe as a whole is formed as a curved plate with symmetry in the right-left width direction and whereof the bottom is the center line in the longitudinal direction.

[0029] Light source 3 comprises as its constituent elements reflective plate 9, base plate 10 for LED elements (hereinafter termed simply "base plate 10") and the required number of white LED elements 11, and is formed as a plate-type light source with a shape corresponding to the transverse sectional shape of the interior of the above-mentioned outer casing. Referring to FIG. 5 and FIG. 7, reflective plate 9 is a plate of a metal such as aluminium. A plate of prescribed shape is used, and the front reflective surface of the plate 9 has a specular finish. Reflective plate 9 moreover formed by a perforated plate in which holding holes have been made in a matrix-like array of prescribed pitch, the number of holding holes so formed being equal to the prescribed number of white LED elements 11 to be used. Examples of this embodiment would be a perforated mirror plate in which the holding holes have been made in a matrix-like array with a staggered configuration, a checker-board configuration, etc., and where the criterion for hole pitch is to add a gap of 7 mm to the outer diameter of a white LED element 11.

[0030] Each of a prescribed number of bullet-shaped white LED elements 11 is inserted and held in a respective holding hole and thus fixed in reflective plate 9. However, as shown in FIG. 8, in this embodiment dimensions are determined and fixed so that the front face of reflective plate 9 is positioned 2 to 4 mm (d0 in FIG. 8) behind electrode portion 12. The reason for this positioning is simply that the described position of reflective plate 9 gives the optimum conditions for minimizing attenuation of the light emitted by electrode portion 12 and for ensuring that the emitted light is efficiently reflected in a forward direction.

[0031] Base plate 10 is a conventional circuit board. A prescribed number of very small holes are made in base plate 10 in a prescribed arrangement which corresponds to positive terminals 23 and negative terminals 24 of white LED elements 11. These terminals consist of fine conductive wires. Base plate 10 is disposed parallel to and directly behind reflective plate 9, and the above-mentioned very small holes are used to attach positive terminals 23 and negative terminals 24 of white LED elements 11 to base plate 10 by means of solder 25. A series-parallel electrical network suitable for the applied voltage is formed at the positive and negative terminals.

[0032] Looking in more detail at light source 3 with the configuration described above, and referring to FIG. 5, because the portion of light source 3 which is housed in rectangular rear portion 7A is relatively wide, reflective plate 9 and base plate 10 of this portion are formed into a bent plate having a wide half-angled gutter shape cor-

responding to the rectangular curved plate of rear portion 8A of globe B. On the other hand, in the portion of light source 3 which is housed in elongated trapezoidal front portion 7B, reflective plate 9 and base plate 10 are formed as flat plates with elongated trapezoidal shapes corresponding to the elongated trapezoidal curved plate of front portion 8B of globe B. The entirety of light source 3 thus configured is housed in lamp casing 7 and positioned therein so that a gap d1 of approximately 20 mm (see FIG. 7) is maintained between light source 3 and globe 8. In a preferred embodiment d1 indicates a minimal clearance between light source 3 and globe 8.

[0033] Light source controller 6 is a control system for controlling several functions including turning light source 3 on and off, charging and discharging the storage battery of power source device 4, and connecting and disconnecting solar cell 5. Light source controller 6 is provided with control command elements such as a timer and a daylight sensor, automatic voltage sensing means for sensing the output voltage of solar cell 5, and automatic electrical storage means which uses the automatic voltage sensing means to cause electric power obtained from solar cell 5 to accumulate in the storage battery. Light source controller 6 is also provided with light source control means for turning light source 3 on and off and for adjusting the amount of emitted light, on the basis of control commands generated by the above-mentioned control command elements. As shown schematically in FIG. 7, light source controller 6, in which these various functional components are integrated, is housed in the vacant space behind light source 3 inside lamp casing 7, with electrical connections to light source 3, power source device 4 and solar cell 5.

[0034] The structure of the principal parts of a white LED lighting device according to an embodiment of the invention has now been described. However, the part referenced 16 in FIG. 2 and FIG. 5 is a heat shield plate and may be added to lamp body 1 if required. This optional heat shield plate 16 is a pressed metal plate made of aluminium or the like and has a shape similar to the planar external shape of lamp body 1. It is mounted in the form of a sunshade directly above lamp casing 7 but leaving a slight air gap between the heat shield plate and the lamp casing. The provision of heat shield plate 16 in this way suppresses temperature rise inside lamp body 1 caused by direct exposure of lamp body 1 to sunlight.

[0035] Lamp support 2 is preferably formed from a hollow pipe. In this case, an air vent (not illustrated) is opened by conventional means in the pipe wall close to the upper end of the support, thereby enabling the hollow portion within the support to produce a chimney effect, with the result that heat generated by the ambient air temperature can be discharged from the air vent. This prevents a temperature rise, stabilizes the performance of the storage battery and extends battery life.

[0036] The parts referenced 19 and 20 in FIG. 2 and FIG. 3 are air inlets and air outlets, respectively. Air inlet

19 opens in the rear face of the side plate in rear portion 7A of lamp casing 7, while air outlet 20 opens in the side face of the side plate in rear portion 7A. Air that has entered through air inlet 19, which is provided at a lower level than air outlet 20, passes through the inside of lamp casing 7 and exits from air outlet 20, whereby rise in temperature inside the casing is suppressed by natural ventilation. This serves to stabilize the performance of the light source controller 6 and the white LED elements 11, which are sensitive to temperature conditions.

[0037] The operation of the device provided by this invention and having the configuration described above will now be described. Lamp body 1 supported by lamp support 2 is for example fixed in a position approximately 3 to 4 m directly above the sidewalk and in a position such that its illuminating surface is directed downward and its axis in the longitudinal direction extends forwards with a slight upward tilt. In the example shown in FIG. 6, lamp body 1 is fixed so that it extends forwards with an upward angle of inclination $\theta 1$ equal to 10 degrees from horizontal. It may be noted that in the lighting device shown in FIG. 6, light source 3 in the front portion 7B of lamp casing 7 is provided in such a manner that it inclines upward at an angle $\theta 2$ equal to 5 degrees relative to the above-mentioned longitudinal direction axis (x), and consequently light source 3 in the front portion 7B extends forwards with an upward angle of inclination $\theta 3$ equal to 15 degrees from horizontal.

[0038] Lamp body 1 installed as described above lights up in the interval from sunset to sunrise under automatic control by light source controller 6. In this embodiment, all the required electric power can be supplied by solar energy, by storing the electric power obtained from solar cell 5 in the storage battery of power source device 4 via light source controller 6. The present lighting device, having high luminance white LED elements 11 as its light source, provides the same level of brightness as a conventional fluorescent light with only approximately one third of the energy consumption. Other advantages are that long-term (approximately 13 years) operation with no bulb burn-outs is achievable; attraction to insects is very slight because the wavelength of the emitted light is close to that of sunlight; and illuminance can be maintained even in cold regions where fluorescent lights will not work.

[0039] An advantage worth special mention is the remarkable enlargement of the irradiation area of lamp body 1. Namely, thanks to the "thick quasi-T" shape design, which is so suitable for a lighting device, and to the synergism - shown schematically in FIG. 7 - between the optical reflection capability of reflective plate 9 and the optical refraction capability of the corrugations and curved plate of globe 8, light which has passed through globe 8 diffuses over a wide area. As a result, the effective irradiation range as projected onto the ground - measuring this range outwards from a point directly below the lighting device - is a fairly long approximately elliptical region with a width that is approximately twice

the depth from front to back. It is therefore possible to obtain an enlarged irradiation range and an illuminance distribution which is ideal for streetlights. Another feature of lamp body 1 is that the entire illuminating surface of globe 8 shines with a uniform brightness which is gentle on the eyes.

[0040] FIG. 9 shows the illuminance distribution as measured on the ground during operation of a white LED lighting device according to this embodiment of the invention. For these measurements, lamp body 1 was positioned at a height of 3450 mm directly above the sidewalk, with its illuminating surface directed downward and its axis (x) in the longer or longitudinal direction extending forwards with an upward angle of inclination θ_1 equal to 10 degrees from the horizontal. Lamp body 1 employed 120 white LED elements (NSPW5008S, luminous intensity 9.20 cd per LED) arranged in a staggered configuration, giving a power consumption of about 10 W.

[0041] According to FIG. 9, an illuminance of 42.6 lux was obtained directly beneath lamp body 1, and this decreased (to 35.0 lux, 20.0 lux and 5.0 lux) with increasing distance. In the lamp body 1 longitudinal direction (i.e., in the road width direction), an illuminance of 1.5 lux was obtained at distances of up to 2.3 m on the roadway side and at distances of up to 3.3 m on the opposite side. In the lamp body 1 width direction (i.e., in the lengthwise direction of the road), an illuminance of 1.5 lux was obtained at distances of up to 5.3 m in both forward and backward directions. In a comparison test conducted under the same conditions with the exception that both the inner and outer surfaces of globe 8 of lamp body 1 were made smooth curved surfaces instead of one being a concavo-convex surface, an illuminance of 1.5 lux was confirmed at distances of up to 3 m in the lamp body 1 width direction (i.e., in the lengthwise direction of the road), in both forward and backward directions. As is evident from these comparative results, there is a particularly striking increase in the effective irradiation range in the width direction of lamp body 1, thereby confirming the advantageousness of the lighting device of the present invention.

[0042] As has now been described, in the present invention, the apparent increase in the number of white LED elements 11 and the effective optical reflection - these characteristics being obtained by the use of a reflective plate in the light source for white LED lighting - in conjunction provide an efficient and loss-free frontal irradiation. This makes it possible to maintain ample illuminance while minimizing the number of white LED elements 11. Accordingly, the light source for white LED lighting of the invention is advantageous in application to white LED lighting devices such as streetlights.

[0043] Moreover, as regards the white LED lighting device of the invention, thanks to a design which is suitable for lighting devices, and thanks to the synergism between the optical reflection capability of the reflective plate and the optical refraction capability of the corruga-

tions and curved plate of the globe, the effective irradiation range as projected onto the ground - measuring this range outwards from a point directly below the lighting device - is an approximately elliptical shape whereof the width is greater than the length from front to back. It is therefore possible to obtain an enlarged irradiation range and an illuminance distribution which is ideal for streetlights. Another advantage of the white LED lighting device of the invention is that it is clearly different from a cluster of spotlights or the like, in that the entire illuminating surface of the globe shines with a uniform brightness which is gentle on the eyes. Furthermore, the present invention can provide a lighting device which compares favorably with a conventional fluorescent light in terms of energy consumption.

[0044] Again, because the present invention uses white LED elements for the light source, ample illuminance can be guaranteed over long periods of time at low power loads; overall, low running costs can be maintained; and an energy-saving, maintenance-free lighting device can be realized.

[0045] Yet another advantage of the invention is that by providing both power source device 4, which has a storage battery, and solar cell 5, all the electric power required to light the lighting device during the night can be supplied by means of solar energy alone, and hence the invention contributes to reducing the consumption of electric power and also eliminates the laying of power cables. Furthermore, selection of installation sites is less restricted and installation work is simplified. The present invention will therefore certainly play a significant role in improving streets and their surrounding environments.

35 Description of reference numerals

[0046]

- 1 lamp body
- 2 lamp support
- 3 light source for white LED lighting
- 4 power source device
- 5 solar cell
- 6 light source Controller
- 7 lamp casing
- 7A rear Portion of lamp casing
- 7B front Portion of lamp casing
- 8 globe
- 8A rear portion of globe
- 8B front portion of globe
- 9 reflective plate
- 10 base plate for LED elements
- 11 white LED element
- 12 electrode portion
- 13 mounting base
- 14 support arm
- 15 bearing portion at bottom end
- 16 heat shield plate

- 17. smooth surface
- 18. concavo-convex banded surface
- 19. air inlet
- 20. air outlet

Captions an drawings

[0047]

- FIG. 5 "direction of light"
- FIG. 6 "direction of light"
- FIG. 7 "refraction of light"
- FIG. 9 [caption on both horizontal and vertical axes: "distance (m)"]

Claims

1. A method for fabricating a light source for white LED lighting, comprising the steps of:

- (i) inserting and holding a plurality of white LED elements (11) in holding holes in a reflective plate (9), said plate (9) being formed by providing a required number of said holding holes, in a matrix-like array of prescribed pitch, in a plate of a shape corresponding to the illuminating surface of a lamp body (1);
- (ii) fixing said plurality of white LED elements (11) at locations 2 to 4 mm behind their respective electrode portions (12);
- (iii) attaching the positive and negative terminals (23, 24) of the white LED elements (11) to a base plate (10) for the LED elements, said base plate being disposed parallel to and directly behind the reflective plate (9); and
- (iv) forming, at the positive and negative terminals (23, 24), a series-parallel electrical network suitable for the applied voltage.

2. A white LED lighting device comprising:

- (A) a lamp body (1) provided with a lamp casing (7), a colourless transparent globe (8) matchingly fixed to an opening in the bottom of said lamp casing, a light source (3) for white LED lighting housed in the lamp casing, and a light source controller likewise housed in the lamp casing;
- (B) a lamp support (2) for supporting the lamp body (1) in a position such that the illuminating surface of said lamp body is directed downward and its axis (x) in the longitudinal direction extends forwards with a slight upward tilt; and

(C) a power source device (4) housed in the lower part of the lamp support and supplying electric power to the light source (3) for white LED lighting;

said white LED lighting device characterized in that:

(D) the lamp casing (7) and the globe (8) have, in those parts facing the light source for white LED lighting, a transverse sectional shape which is rectangular in the rear portions (7A, 8A) that lie towards a mounting base (13), the sides of said rectangular shape being parallel to said longitudinal direction (x) and being the short sides of the rectangular shape, and which is an elongated trapezoid in the front portions (7B, 8B) that are adjacent to the rear portions (7A, 8A);

(E) the inside of the illuminating surface of the globe (8) is a smooth surface, the outside is a longitudinally banded concavo-convex surface (18) consisting of adjoining ridges and valleys alternating in succession with a pitch of a few millimeters, and the illuminating surface of the globe (8) as a whole is formed as a curved plate with bilateral symmetry whereof the bottom is the center line in said longitudinal direction;

(F) the light source (3) for white LED lighting is comprises:

- (i) a plurality of white LED elements (11) inserted in holding holes in a reflective plate (9), said plate providing a required number of said holding holes in the form of a multi-row, multi-column array of prescribed pitch;
- (ii) said plurality of white LED elements located at locations 2 to 4 mm behind their respective electrode portions (12);
- (iii) positive and negative terminals (23, 24) of the white LED elements attached to a base plate (10) for the LED elements (11), said base plate being disposed parallel to and directly behind the reflective plate; and
- (iv) a series-parallel electrical network formed at the positive and negative terminals suitable for the applied voltage;
- (G) the reflective plate (9) and the base plate (10) for the LED elements in said rear portions (7A, 8A) are formed into a bent plate having a wide half-angled gutter shape corresponding to said curved plate;
- (H) the reflective plate (9) and the base plate (10) for the LED elements in said front portions (7B, 8B) are formed into an elongated trapezoidal flat plate corresponding to said curved plate; and
- (I) the intrinsic irradiation range of the lamp body (1) is enlarged on the basis of a synergism between the optical reflection capa-

bility of the reflective plate (9) and the optical refraction capability of the corrugations and curved plate of the globe (8).

3. The white LED lighting device of Claim 2, wherein: 5

a solar cell (5) is mounted and fixed at the upper end of the lamp support (2);
the power source device (4) is provided with a storage battery; and 10
the light source controller (6) is provided with automatic voltage sensing means for sensing the output voltage of the solar cell (5), and with automatic electrical storage means which uses said automatic voltage sensing means to cause electric power obtained from the solar cell (5) to accumulate in the storage battery. 15

4. The white LED lighting device of Claim 3, wherein: 20

the lamp support (2) is formed from a hollow pipe and provided with an air vent in the pipe wall close to the upper end, thereby enabling the hollow portion to produce a chimney effect so that heat generated by ambient air temperature can escape. 25

5. The white LED lighting device of Claim 3 or Claim 4, wherein: 30

the lamp body is provided with a metal heat shield plate (16) mounted in the form of a sunshade directly above the lamp casing (7) but leaving a slight air gap between said heat shield plate and the lamp casing. 35

6. The white LED lighting device of Claim 5, wherein:

the lamp body (1) is provided with air inlets and air outlets (19, 20) in the rear and side faces of the side plate in said rear portions of the lamp casing. 40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

